

Central I/O module, SpaceLogic, 8 analog outputs

SXWAO8XXX10001

Main

Device short name	AO-8
Product or component type	I/O module
Net weight	159 g
Flame retardance	UL94V0-5VB
Height	114 mm
Product certifications	ICES-003 FCC part 15 class B CE RCM
Width	90 mm
Depth	64 mm
Ambient air temperature for operation	050 °C
IP degree of protection	IP20
Ambient air temperature for storage	-2070 °C
Power consumption in W	4.9 W
Relative humidity	095 % non-condensing
Number of outputs	8 analog output
[Us] rated supply voltage	24 V DC
Product name	I/O Modules
Product brand	Schneider Electric
Range	EcoStruxure Building Operation

Complementary

Control type	Without
Electrical connection	Plug-in sub-base
Mounting support	DIN rail Wall
Analogue input type	Configurable voltage or current 020 mA Configurable voltage or current 010 V input voltage
Range compatibility	EcoStruxure Building Operation TB-IO-W1 terminal base
Standards	UL 864 UL 916

-	
Material	ABS + PC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	11.7 cm
Package 1 Length	9.0 cm
Package 1 Weight	158.0 g

Offer Sustainability

- · · · - · · - · · · · · · · · · · · ·	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product

Recommended replacement(s)