

Central I/O module, SpaceLogic, 12 Form A digital outputs

SXWDOA12X10001

Main

Device short name	DO-FA-12
Product or component type	I/O module
Net weight	194 g
Flame retardance	UL94V0-5VB
Height	114 mm
Product certifications	ICES-003 FCC part 15 class B CE RCM
Width	30 mm
Power consumption in VA	1.8 W
Depth	64 mm
Ambient air temperature for operation	050 °C
IP degree of protection	IP20
Ambient air temperature for storage	-2070 °C
Relative humidity	095 % non-condensing
Product name	I/O Modules
Product brand	Schneider Electric
Range	EcoStruxure Building Operation

Complementary

Control type	Without
Electrical connection	Plug-in sub-base
Discrete output number	12
Discrete input voltage	24 V
Discrete output type	Relay
Mounting support	DIN rail Wall
Local signalling	LED (green) for relay energised
Range compatibility	EcoStruxure Building Operation TB-IO-W1 terminal base

Standards	UL 864
	UL 916 FCC CFR 47 part 15
Material	ABS + PC
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	5.7 cm
Package 1 Length	11.8 cm
Package 1 Weight	196.2 g
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

The product must be disposed on European Union markets following specific waste collection and

China RoHS declaration

End of Life Information

Product Environmental Profile

never end up in rubbish bins

Halogen free plastic parts & cables product

Yes

Yes

Recommended replacement(s)

Halogen content performance

China RoHS Regulation

RoHS exemption information

Environmental Disclosure

Circularity Profile

WEEE

PVC free