

Product datasheet

Specifications



Analogue addressable fire alarm panel, Esmi Ultima, 2-8 loop, 240V

FFSULH1001

Main

Range of product	Esmi fire detection panels UL
Product or component type	Fire control panel

Complementary

Maximum supply current	5.25 A 24 V DC 10.25 A 24 V DC
[Us] rated supply voltage	240 V AC
Battery capacity	28 Ah
Colour	Box: red Lid: red Plate: anthracite grey (RAL 7016)
Discrete input number	3 programmable discrete input(s)
Output type	5 relay output at 1 A, 30 V and DC 2 auxiliary output at 900 mA, 24 V and DC 4 NAC: class B at 2.5 A 2 NAC: class A at 2.5 A
Current consumption	400 mA loop circuit
Display type	LCD touch screen
Display resolution	800 x 600 pixels
Height	590 mm
Width	420 mm
Depth	153 mm
Number of SLC loops	2...8
Maximum number of connected panels	127

Environment

Product certifications	UL listed FM
------------------------	-----------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	13.6 kg

Package 1 Height	74.3 cm
Package 1 width	52.1 cm
Package 1 Length	31.1 cm