

Product datasheet

Specifications



Current Switch: Split Core, H608-S6, 0.5 to 175 A continuous, N.O. 1.0 A at 30 VAC/VDC, not polarity sensitive, not polarity sensitive, Adjustable

3240103000

Main

Range Of Product	HX08 Series
Product Or Component Type	Sensor
Sensor Model	H608-S6
Type Of Measurement	AC current
Device Application	Building automation systems
Current Measurement Range	0.5...175 A
Sensor Type	Current switch, AC
Awg Gauge	AWG 24...AWG 14
Network Frequency	50...60 Hz
Opening Width	12 mm
Mounting Support	Split core housing
Relative Humidity	10...90 % RH, non-condensing
Ambient Air Temperature For Operation	-15...60 °C
Output Current	1 A at 30 V AC/DC
Output Type	Switch output
Product Certifications	UL CE
Setpoint	Yes
Targeted Region	Europe Asia Pacific.

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.9 cm
Package 1 Width	6.4 cm
Package 1 Length	8.9 cm
Package 1 Weight	90.7 g

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations